

# **Tecnoflon® PFR 95** perfluoroelastomer

Tecnoflon® PFR 95 is a perfluoroelastomer (FFKM) offering wide operational range and superior compression set resistance, thanks to its unique peroxide curing system that does not need any coagent (TAIC or equivalent) for curing to be carried out.

Thanks to its curing system, it can offer a very broad chemical resistance in a wide variety of media including acids, caustics, ketones, aldehydes, esters, ethers, methanol, solvents, sour gases, hydrocarbons, steam, hot water and mixed process streams along with excellent thermal resistance.

Tecnoflon® PFR 95 is suitable for most applications in temperature ranging from -10 °C to 280 °C.

Tecnoflon® PFR 95 can be combined with other typical fluoroelastomer compounding ingredients; its mixing can be accomplished with two-roll mills or internal mixers. Finished goods may be produced by a variety of rubber processing methods.

The primary use for Tecnoflon® PFR 95 is the manufacturing of any kind of elastomeric sealing element such as O-rings, gaskets, valve bodies, butterfly valves,

pump housings and stators, metal bonded parts, diaphragms, profiles, etc. These sealing elements can be used in mechanical seals, pumps, compressors, valves, reactors, mixers, sprayers, dispensers, quick connect couplings, controls, instrumentation, etc. in chemical and petrochemical industry, hydrocarbon processing, petroleum exploration and extraction, food processing, pharmaceutical and bio-analytical industry, aerospace and semiconductor manufacturing industries.

Tecnoflon® PFR 95 is registered in the FDA Inventory of Effective Premarket Notifications for Food Contact Substances. It can be compounded so that the finished gaskets or seals can be used in food processing equipments (see "food processing compounds" section below).

Tecnoflon® PFR 95 is marketed in the form of raw polymer (1 kg box) in order to give the transformer the freedom and the opportunity to develop and fine-tune compounds and items best suited to produce high performance rubber articles such as O-rings, seals, diaphragms and other parts used in process industries.

## **General**

Material Status	• Commercial: Active		
Availability	• Europe	• North America	
Features	• Acid Resistant • Alcohol Resistant • Food Contact Acceptable • Fuel Resistant	• Good Chemical Resistance • High Heat Resistance • Low Compression Set • Moisture Resistant	• Solvent Resistant • Steam Resistant
Uses	• Blending • Compounding • Diaphragms	• Gaskets • Profiles • Pump Parts	• Seals • Valves/Valve Parts
Agency Ratings	• FDA Food Contact, Unspecified Rating		
Appearance	• Translucent		
Forms	• Slab		
Processing Method	• Compounding		

## **Physical**

	Typical Value	Unit	Test method
Mooney Viscosity <sup>1</sup> (ML 1+10, 121°C)	35	MU	No Standard

# Tecnoflon® PFR 95

perfluoroelastomer

---

## Notes

Typical properties: these are not to be construed as specifications.

<sup>1</sup> Raw polymer



**[www.solvay.com](http://www.solvay.com)**

**[SpecialtyPolymers.EMEA@solvay.com](mailto:SpecialtyPolymers.EMEA@solvay.com)** | Europe, Middle East and Africa

**[SpecialtyPolymers.Americas@solvay.com](mailto:SpecialtyPolymers.Americas@solvay.com)** | Americas

**[SpecialtyPolymers.Asia@solvay.com](mailto:SpecialtyPolymers.Asia@solvay.com)** | Asia and Australia

Material Safety Data Sheets (MSDS) are available by emailing us or contacting your sales representative. Always consult the appropriate MSDS before using any of our products. Neither Solvay Specialty Polymers nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this product, related information or its use. Some applications of which Solvay's products may be proposed to be used are regulated or restricted by applicable laws and regulations or by national or international standards and in some cases by Solvay's recommendation, including applications of food/feed, water treatment, medical, pharmaceuticals, and personal care. Only products designated as part of the Solviva® family of biomaterials may be considered as candidates for use in implantable medical devices. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. All trademarks and registered trademarks are property of the companies that comprise the Solvay Group or their respective owners.

© 2013 Solvay Specialty Polymers. All rights reserved.